

TITAN ATF DEX III

Universal DEXRON III ATF for all automatic transmissions in commercial vehicles, machinery and passenger cars according to manufacturer's recommendation.

Description

TITAN ATF DEX III is an Automatic Transmission Fluid (ATF) with performance level DEXRON III and thus suitable for a large variety of applications. It is formulated on selected mineral base-oils and offers safe operation even under high stress in automatic transmissions, power steering systems and other hydraulic systems.

Application

TITAN ATF DEX III is miscible and compatible with conventional branded ATFs. However, a

complete oil change is recommended when converting to TITAN ATF DEX III in order to exploit the product's full benefits.

Advantages/Benefits

- Protects against wear, sludge, adhesions and corrosion and offers outstanding, shear-stable viscosity-temperature properties.
- Capable of high thermal stress and does prevent successfully from foam
- TITAN ATF DEX III is compatible with many seal materials

CHARACTERISTICS

Properties	Unit	Value	Test Method
Density @ 15 °C	g/ml	0.860	ASTM D 4052
Flash Point, COC	°C	190	ASTM D 92
Pour Point	°C	-39	ASTM D 97
Kinematic Viscosity @ 40 °C	mm ² /s	35.85	ASTM D 445
Kinematic Viscosity @ 100 °C	mm ² /s	7.2	ASTM D 445
Brookfield @ - 40 °C	cP	45000	ASTM D 2983

Dhaka Office :
37, Suhrawardy Avenue
Baridhara, Dhaka 1212,
Bangladesh
Phone : 88 02-9858465, 9858559
Fax : 8802-9858465, 9858559, Extn.-112
Website : www.fuchsb.com

Plant :
BSCIC Industrial Estate
Block-A, Sagarika Road, Chittagong 4219
Bangladesh.
Phone : 88-031-2770060,2770446,2773840
Fax : 88-031-2770061

