

TITAN SUPER FORMULA 20W50

Super Performance motor oil for passenger cars.

Description

TITAN SUPER FORMULA oils are super premium quality, mono/multi-grade engine lubricants suitable for, and meeting the performance requirements of American, European and Asian car manufacturers.

TITAN SUPER FORMULA oils are formulated from highest quality base oils blended with a proven shear-stable viscosity index improver to give fluidity and easy starting in winter, together with good lubrication and low oil consumption at high operating temperatures. They contain a unique low ash, detergent additive package that keeps pistons and rings deposit-free despite adverse peak temperatures. This additive package also disperses and neutralizes harmful acid sludge formed during cold running. Scuffing and undue wear of rings, bores and valve train components are prevented by special anti-wear agents. Additional additive treatment minimizes oil thickening, helps prevent the formation of deposits at high temperatures and gives excellent protection against rust, corrosion and foaming.

Application

Modern automotive engines are subjecting the motor oil to increasingly severe conditions. Increased power output, extended drain intervals, more stop-go operation and high operating temperatures are additional factors influencing the need for higher motor oil quality. TITAN SUPER FORMULA oils have been specially developed to cope with these arduous conditions using stringent performance tests.

TITAN SUPER FORMULA 20W50 is suitable for year round use in all four-stroke petrol engines, including those with positive crankcase ventilation (PCV) and other anti-pollution devices. It is equally satisfactory in all normally aspirated diesel engines.

Specifications

API SG/CF

TITAN SUPER FORMULA

Properties	Unit	Value	Test Method
SAE Grade		20W-50	DIN 51 511
Density @ 15 °C	g/ml	0.883	ASTM D 4052
Flash Point, COC	°C	238	ASTM D 92
Pour Point	°C	-24	ASTM D 97
Dynamic Viscosity @ - 15 °C	mPa.s	8500	ASTM D 5293
Kinematic Viscosity @ 40 °C	mm ² /s	180	ASTM D 445
Kinematic Viscosity @ 100 °C	mm ² /s	19.2	ASTM D 445
Viscosity Index	-	121	ASTM D 2270
TBN	mg KOH/g	5	ASTM D 2896

Dhaka Office :
37, Suhrawardy Avenue
Baridhara, Dhaka 1212,
Bangladesh
Phone : 88 02-9858465, 9858559
Fax : 8802-9858465, 9858559, Extn.-112
Website : www.fuchsb.com

Plant :
BSCIC Industrial Estate
Block-A, Sagarika Road, Chittagong 4219
Bangladesh.
Phone : 88-031-2770060, 2770446, 2773840
Fax : 88-031-2770061

