

TITAN SUPER GT 20W-50

High-performance, gasoline passenger cars oil

Description

TITAN SUPER GT is premium quality multi-grade oil for Gasoline Engines with and without Turbo charging. It meets service requirements of the API Engine Service Classification. SL, TITAN SUPER GT 20W-50 and 10W-30 bear API donut. They are also certified by Saudi Arabian Standard Organization (SASO) and bears a SASO quality seal.

Advantages/Benefits

- Improved high temperature deposit control resulting in longer engine life and better turbo-charge performance
- Excellent protection against wear due to improved lubrication film even at full-throttle operations
- Protects against Bore Polishing
- Optimise function of Hydraulic Tappets with no foaming.
- Compatible with gaskets and seals.

Application

TITAN SUPER GT is recommended for year round use in passenger cars, light duty trucks and vans with naturally aspirated or turbocharged gasoline engines. It can also be used in light duty diesel engines.

Specifications

- API SL/CF

Follow the equipment manufacture's recommendations for required lubricant performance levels and viscosity grades.

TITAN SUPER GT is available in three different viscosity grades TITAN SUPER GT 20W-50, TITAN SUPER GT 10W-40 and TITAN SUPER GT 10W-30 to meet all new advanced engines requirement.

TITAN SUPER GT 20W-50

Density @ 35 °C	0.879	g/ml	ASTM D 4052
Flash Point, COC	246	°C	ASTM D 92
Pour Point	-24	°C	ASTM D 97
Kinematic Viscosity @ 40 °C	173	mm ² /s	ASTM D 445
Kinematic Viscosity @ 100 °C	19.5	mm ² /s	ASTM D 445
Viscosity Index	129	-	ASTM D 2270

Dhaka Office :
37, Suhrawardy Avenue
Baridhara, Dhaka 1212,
Bangladesh
Phone : 88 02-9858465, 9858559
Fax : 8802-9858465, 9858559, Extn.-112
Website : www.fuchsb.com

Plant :
BSCIC Industrial Estate
Block-A, Sagarika Road, Chittagong 4219
Bangladesh.
Phone : 88-031-2770060, 2770446, 2773840
Fax : 88-031-2770061

