

TITAN TRUCK PLUS SAE 15W-40

High Performance oil for a variety of diesel and gasoline engines. Specially for highly loaded commercial vehicle diesel engines. Lower oil consumption.

Description

TITAN TRUCK PLUS SAE 15W-40 is a super-long term all-season engine oil of the SHPD category for diesel and gasoline engines with and without turbo-charging in passenger cars, trucks, buses and industrial equipment that have high requirements intervals. TITAN TRUCK PLUS SAE 15W-40 complies with and/or fulfills and exceeds the requirements of American and European engine manufacturers thanks to its special design, especially engines with fill and VOLVO VDS-3. Because of its advanced design, TITAN TRUCK PLUS SAE 15W-40 ensures operation without problems under all climatic conditions.

Application

TITAN TRUCK PLUS SAE 15W-40 has a significantly more modern alloy than the usual HD engine oils of the same SAE class. Independently of the odometer reading, all commercial vehicle diesel engines can be changed over to TITAN TRUCK PLUS SAE 15W-40 without flushing. Used TITAN TRUCK PLUS SAE 15W-40 is safe to dispose of as old oil since it is assigned to "old oil category 1". Important for shipping companies, contraction companies, etc. is also that TITAN TRUCK PLUS SAE 15W-40 can be used even with higher sulfur content in the diesel fuel, while with the usual HD engine oils this can often lead to considerable problems. TITAN TRUCK PLUS SAE 15W-40 is best suitable for use in EURO 3 engines.

Advantages/Benefits

- Excellent wear protection even under high continuous stress.
- Protection from corrosion even when used with diesel fuels with high sulfur content
- Sludge and adhesions are securely prevented by TITAN TRUCK PLUS SAE 15W-40 both with extraordinarily high thermal loads as well as in stop and- go driving.

Specifications

- ACEA E7
- API CI-4
- GLOBAL DHD-1
- CAT ECF-1-a/EECF-2

Approvals

- CUMMINS CES 20076/7/8
- DEUTZ DQC III
- MAN M 3275-1
- MB-APPROVAL 228.3
- MTU DDC TYPE-2
- RENAUL RLD / RLD- 2
- VOLVO VDS-3
- MACK EO-M PLUS.

FUCHAS Recommendations

- ALLISON C-4
- CAT TO-2
- CASE MS 1121
- IVECO 18-1804 CLASSE T2 E7
- DAF
- CUMMINS CES 20071/2
- STEYR A-201
- NH 330 H

Dhaka Office :

37, Suhrawardy Avenue
Baridhara, Dhaka 1212,
Bangladesh
Phone : 88 02-9858465, 9858559
Fax : 8802-9858465, 9858559, Extn.-112
Website : www.fuchsb.com

Plant :

BSCIC Industrial Estate
Block-A, Sagarika Road, Chittagong 4219
Bangladesh.
Phone : 88-031-2770060,2770446,2773840
Fax : 88-031-2770061



CHARATERISTICS

Properties	Unit	Value	Test Method
SAE Grade		15W-40	DIN 51 511
Density @ 15 °C	g/ml	0.875	ASTM D 4052
Flash Point, COC	°C	226	ASTM D 92
Pour Point	°C	-30	ASTM D 97
Kinematic Viscosity @ 40 °C	mm ² /s	110	ASTM D 445
Kinematic Viscosity @ 100 °C	mm ² /s	14.8	ASTM D 445
Viscosity Index	-	139	ASTM D 2270
Dynamic Viscosity @ - 20 °C	mPa.s	6560	ASTM D 5293
TBN	mg KOH/g	10	ASTM D 2896

Dhaka Office :
37, Suhrawardy Avenue
Baridhara, Dhaka 1212,
Bangladesh
Phone : 88 02-9858465, 9858559
Fax : 8802-9858465, 9858559, Extn.-112
Website :www.fuchsgbd.com

Plant :
BSCIC Industrial Estate
Block-A, Sagarika Road, Chittagong 4219
Bangladesh.
Phone : 88-031-2770060,2770446,2773840
Fax : 88-031-2770061

