

FUCHS MAL GREASE **(Aluminium Grease)**

Aluminium based grease having the resistance to water washout and corrosion and not suitable for high thermal load.

Description

FUCHS MAL GREASE is good quality Aluminium soap based grease made of Aluminium stearate and high quality base stock. The grease is very translucent & resistant to water and protects against corrosion. The lower NLGI grades can be

applied by automatic dispensing equipment. The Grease is suitable for plain bearing and chasis lubrication. The operating Temperatures should not exceed 60°C. At an elevated temperature the Grease tends to become rubbery.

Product Characteristics

Properties	Unit	Value		
NIGI Grade		No.1	NO.2	No.3
Soap Type		Aluminium	Aluminium	Aluminium
Penetration, @ 25°C, Worked	60 Strokes, typical	320	275	240
Dropping Point, min	°C	97	98	100
Base Oil Viscosity, @ 40°C, min	cSt	100	100	100

Dhaka Office :
37, Suhrawardy Avenue
Baridhara, Dhaka 1212,
Bangladesh
Phone : 88 02-9858465, 9858559
Fax : 8802-9858465, 9858559, Extn.-112
Website : www.fuchsgbd.com

Plant :
BSCIC Industrial Estate
Block-A, Sagarika Road, Chittagong 4219
Bangladesh.
Phone : 88-031-2770060, 2770446, 2773840
Fax : 88-031-2770061

