Product Information



TITAN SUPER GEAR 80W-90

High Performance Gear Oil for extended oil change intervals.

Description

TITAN SUPERGEAR 80W-90 is a mineral universal gear oil for use in manual transmissions and axle gearboxes in both passenger cars and commercial vehicles.

Application

TITAN SUPERGEAR 80W-90 is miscible and compatible with conventional branded gear oils. However, mixing with other gear oils should be avoided in order to fully utilize the product's benefits. A complete oil change is recommended when converting to TITAN SUPERGEAR 80W-90. For information on product safety and proper disposal please refer to the latest Material Safety Data Sheet.

Specifications

• API GL-4/GL-5

Approvals ZF TE-ML 05A, 12E, 16D, 21A

Advantages/Benefits

- TITAN SUPERGEAR 80W-90 provides good cold flow properties. This supports easy cold starting and easy shifting in the warm-up period. Improved lubrication and excellent protection against wear even during short-distance winter operation.
- TITAN SUPERGEAR 80W-90 creates a stable lubricant film capable of withstanding severe loads.
- Due to the significant shear stability of TITAN SUPERGEAR 80W-90, the oil remains within the 80W-90 viscosity range even after very long periods of use.
- The good corrosion protection provided by TITAN SUPERGEAR 80W-90 protects against rust and attacking of non-ferrous metals.

FUCHS Recommendations

• MIL-L-2105 D

TYPICAL CHARACTERISTICS

Properties SAE Grade	Unit	Value 80W-90	Test Method DIN 51 511
Density at 15 °c	g/ml	0.895	DIN 51 511 DIN 51757
Colour	ASTM	4	DIN ISO 2049
Flash Point, COC	$^{\circ}\mathrm{C}$	220	DIN ISO 2592
Pour Point	$^{\circ}\mathrm{C}$	-27	DIN ISO 3016
Neutralization number	mgKOH/g	1.1	FLV-N7 / DIN 51558
Foaming Tendency Seq. I/II/III	ml	0/0; 0/0; 0/0	ASTM D 892
Dynamic Viscosity at – 12°C	mPa.s	62,000	DIN 51398
Kinematic Viscosity at 40°C	mm^2/s	134	DIN 51562-1
Kinematic Viscosity at 100°C	mm^2/s	14.4	DIN 51562-1
Viscosity Index -		106	DIN ISO 2909

Dhaka Office:

37, Suhrawardy Avenue Baridhara, Dhaka 1212, Bangladesh

Phone: 88 02-9858465, 9858559 Fax: 8802-9858465, 9858559, Extn.-112

Website: www.fuchsbd.com

Plant :

BSCIC Industrial Estate

Block-A, Sagarika Road, Chittagong 4219

Phone: 88-031-2770060,2770446,2773840

Fax : 88-031-2770061

