

Fuchs 4T Motor Oil

4T Motor oil is a superior multi-grade four-stroke motorcycle oil

PERFORMANCE STANDARD

SPC 4T PLUS meets the following performance requirement:

- API SL

BENEFITS

4T Motor Oil provides the following benefits:

- Maintains good detergent-dispersant properties to keep engine clean
- Provides superior protection against oil oxidation and sludge formation
- Exhibits good antifoam and anti-wear properties
- Protects the engine against rust and corrosion
- Good wear protection

APPLICATION

4T Motor oil is suitable for four-stroke motorcycle engines .

TYPICAL CHARACTERISTICS

Properties	Unit	Value	Test Method
SAE Grade		20W-40	DIN 51 511
Kinematic Viscosity @ 40°C	mm ² /s	147	ASTM D445
Kinematic Viscosity @ 100 °C	mm ² /s	15.9	ASTM D445
Dynamic Viscosity at – 15°C	mPa.s	8500	ASTM D5293
Viscosity Index	-	113	ASTM D2270
Density at 15 °C	g/ml	0.882	ASTM D1298
Flash Point, COC	°C	240	ASTM D92
Pour Point,	°C	-24	ASTM D 97

Dhaka Office :
37, Suhrawardy Avenue
Baridhara, Dhaka 1212,
Bangladesh
Phone : 88 02-9858465, 9858559
Fax : 8802-9858465, 9858559, Extn.-112
Website : www.fuchsb.com

Plant :
BSCIC Industrial Estate
Block-A, Sagarika Road, Chittagong 4219
Bangladesh.
Phone : 88-031-2770060,2770446,2773840
Fax : 88-031-2770061

