## **Product Information**



## RENOLIT MP

## (Multipurpose Grease)

A multipurpose Lithium based grease suitable for cases where high temperature and water contamination is encountered and it has excellent resistance to water washout and oxidation.

## Description

Fuchs Renolit MP is an amber colored, buttery smooth lithium grease suitable for a wide range of use. Fuchs Renolit MP has very good mechanical stability and excellent bearings, oxidation stability, ensuring long life. It is specially inhibited against rust and corrosion and has superior resistance to the washing out action of water. Fuchs Renolit MP maintains good pump ability, even in cold weather, and is ideal for centralized grease systems.

Fuchs throughout bearings, other plain temperature of the washing out action of water. Fuchs Renolit MP maintains contamination of the properties of the washing out action of water. Fuchs Renolit MP maintains the properties of the washing out action of water. Fuchs Renolit MP maintains the properties of the washing out action of water. Fuchs Renolit MP maintains the properties of the pro

#### Benefit

The excellent oxidation resistance, as indicated by a low drop in pressure after 500 hours at 99°C and under 110 psi of oxygen indicates longer life in bearing with much less deterioration than greases of lesser quality.

### **Application**

**Fuchs Renolit MP** is true multipurpose grease and is suitable for applications found throughout industry, such as electric motor bearings, fan bearings, pump bearings and other plain and antifriction applications.

- Fuchs Renolit MP is suitable for bearing temperatures up to 120°C,
- It is recommended for use where water contamination is encountered.
- It is suitable to bearings operating at temperatures as high as 120°C or higher, if replenished frequently.
- Its pumpability makes it especially suitable in centralized grease systems, even at low temperatures.

Dhaka Office :

37, Suhrawardy Avenue Baridhara, Dhaka 1212, Bangladesh

Phone: 88 02-9858465, 9858559

Fax: 8802-9858465, 9858559, Extn.-112

Website:www.fuchsbd.com

Plant :

BSCIC Industrial Estate

Block-A, Sagarika Road, Chittagong 4219

Bangladesh.

Phone: 88-031-2770060,2770446,2773840

Fax : 88-031-2770061



# **Product Information**



## **Product Characteristics**

Properties	Unit		Value	
Fuchs Renolit MP		No. 2	No. 3	
Color, Appearance		Yellow,	Yellow, Smooth	
		Smooth		
NLGI Grade		2	3	
Soap Type		Lithium	Lithium	
Worked Penetration @ 25°C	60 stokes, typical	277	230	
Base Oil Viscosity @ 40°C	cSt	130-150	130-150	
Oxidation Stability	Pressure bar	0.3	0.3	
Dropping Point	<sub>0</sub> C	190	196	

Dhaka Office:

37, Suhrawardy Avenue Baridhara, Dhaka 1212, Bangladesh

Phone: 88 02-9858465, 9858559 Fax: 8802-9858465, 9858559, Extn.-112

Website:www.fuchsbd.com

Plant:
BSCIC Industrial Estate

Block-A, Sagarika Road, Chittagong 4219

Bangladesh.

Phone: 88-031-2770060,2770446,2773840

: 88-031-2770061

